

Relés de Potencia Interruptor
Normally Open Power Relays Multi-Purpose
Relais Contacteur Puissance

12V/50Amp.
24V/30Amp.

2

| DESCRIPCIÓN | CÓDIGO | REFERENCIA | WVE | VOLTS | AMP | PROTEC. | TIPO | CONEXIONES |
|---|--------|------------|-----|-------|------|---------|------|--|
|  <p>Relés Interruptores <i>Normally Open Relays</i> <i>Relais Contacteurs</i></p> | 02395 | RLE/4-12 | C | 12 V | 50 A | - | B | <p>Tipo B / Plano 2</p>  <p>2 x 6.3 mm 2 x 8 mm</p>  |
| | 02396 | RLES/4-12 | - | 12 V | 50 A | - | B | |
| | 02803 | RLE/4-12R | C | 12 V | 50 A | — | B | |
| | 02804 | RLES/4-12R | - | 12 V | 50 A | — | B | |
| | 02693 | RLE/4-12D | C | 12 V | 50 A | ◀ | B | |
| | 02807 | RLES/4-12D | - | 12 V | 50 A | ◀ | B | |
| | 02397 | RLE/4-24 | C | 24 V | 30 A | - | B | |
| | 02398 | RLES/4-24 | - | 24 V | 30 A | - | B | |
| | 02805 | RLE/4-24R | C | 24 V | 30 A | — | B | |
| | 02806 | RLES/4-24R | - | 24 V | 30 A | — | B | |
| UNIVERSAL / STANDARD / UNIVERSEL | 02808 | RLE/4-24D | C | 24 V | 30 A | ◀ | B | |
| | 02809 | RLES/4-24D | - | 24 V | 30 A | ◀ | B | |

| TIPO A | TIPO B | SAE | DIN | Aplicaciones |
|--|---|-----------------------|-----------------------------|---|
|  <p>BMW FORD OPEL VOLVO</p> <p>ISO7588</p> |  <p>ALFA RENAULT AUDI ROVER CITROËN SAAB DAIMLER BENZ SEAT FIAT SINCA MAN TALBOT NISSAN VW PEUGEOT</p> <p>ISO8092</p> | 3 2 1 5 4 | 30 85 86 87 87a | <p>Cargas Inductivas y Resistivas <i>Inductive and resistive loads</i> <i>Charges inductives et résistives</i></p>  |