

	No.	Brand Name	Bracket	Volt/Amp.	Type	Socket Type	Term. Config.
	273940	Ripca/Ripaults	loose metal	24V/20A	Normally Open with resistor	B white	4-pin
	2739	Nagares	yes	24V/22A	Normally Open with resistor	B	4-pin
	2740	Nagares	no	24V/22A	Normally Open with resistor	B	4-pin
	2699	Nagares	yes	24V/22A	Normally Open with resistor and double output.	B	5-pin
	2747	Nagares	no	24V/22A	Normally Open with resistor and double output.	B	5-pin

TIPO A	TIPO B	SAE	DIN	Aplicaciones/Applications
<p>BMW FORD OPEL VOLVO</p> <p>ISO7588</p>	<p>ALFA AUDI CITROËN DAIMLER BENZ FIAT MAN NISSAN PEUGEOT</p> <p>RENAULT ROVER SAAB SEAT SINCA TALBOT VW</p> <p>ISO8092</p>	<p>3</p> <p>2</p> <p>1</p> <p>5</p> <p>4</p>	<p>30</p> <p>85</p> <p>86</p> <p>87</p> <p>87a</p>	<p>Cargas Inductivas y Resistivas Inductive and resistive loads Charges inductives et résistives</p>