

Relés Polivalentes Interruptores
Normally Open Relays Multi-Purpose
Relais Contacteurs Polyvalents

12V/70Amp.
24V/40Amp.



Relés Interruptores
Normally Open Relays
Relais Contacteurs


02687	RLAC/4-12	C	12 V	70 A	-	B
02763	RLACS/4-12	-	12 V	70 A	-	B
02810	RLAC/4-12R	C	12 V	70 A	■	B
02811	RLACS/4-12R	-	12 V	70 A	■	B
02814	RLAC/4-12D	C	12 V	70 A	◀	B
02815	RLACS/4-12D	-	12 V	70 A	◀	B
02792	RLAC/4-24	C	24 V	40 A	-	B
02798	RLACS/4-24	-	24V	40 A	-	B
02812	RLAC/4-24R	C	24 V	40 A	■	B
02813	RLACS/4-24R	-	24 V	40 A	■	B
02816	RLAC/4-24D	C	24 V	40 A	◀	B
02817	RLACS/4-24D	-	24 V	40 A	◀	B

UNIVERSAL / STANDARD / UNIVERSEL

Tipo B / Plano 3



2 x 6,3 mm
 2 x 9,5 mm



TIPO A	TIPO B	SAE	DIN	Aplicaciones/Applications
 ISO7588	 ISO8092	ALFA AUDI CITROËN DAIMLER BENZ FIAT MAN NISSAN PEUGEOT	RENAULT ROVER SAAB SEAT SINCA TALBOT VW	Cargas Inductivas y Resistivas <i>Inductive and resistive loads</i> Charges inductives et résistives