

Article	Wire size	Cross sec	eyelet	Length	M measurement	Operational degrees	Materials
TT1.5-6	1.5mm <sup>2</sup>	Ø 6.4mm	14.5mm	M6		90°C	Copper Tinned
TT1010	10.0mm <sup>2</sup>	Ø 10.5mm	41.0mm	M10		90°C	Copper Tinned
TT1012	10.0mm <sup>2</sup>	Ø 12.4mm	41.0mm	M12		90°C	Copper Tinned
TT105	10.0mm <sup>2</sup>	Ø 5.3mm	29.0mm	M5		90°C	Copper Tinned
TT106R	10.0mm <sup>2</sup>	Ø 6.4mm	29.0mm	M6		90°C	Copper Tinned
TT106	10.0mm <sup>2</sup>	Ø 6.4mm	29.0mm	M6		90°C	Copper Tinned
TT108R	10.0mm <sup>2</sup>	Ø 8.4mm	38.0mm	M8		90°C	Copper Tinned
TT108	10.0mm <sup>2</sup>	Ø 8.4mm	38.0mm	M8		90°C	Copper Tinned
TT12010	120.0mm <sup>2</sup>	Ø 10.5mm	72.0mm	M10		90°C	Copper Tinned
TT12012	120.0mm <sup>2</sup>	Ø 12.4mm	72.0mm	M12		90°C	Copper Tinned
TT12016	120.0mm <sup>2</sup>	Ø 16.5mm	72.0mm	M16		90°C	Copper Tinned
TT15010	150.0mm <sup>2</sup>	Ø 10.5mm	74.0mm	M10		90°C	Copper Tinned
TT15012	150.0mm <sup>2</sup>	Ø 12.4mm	74.0mm	M12		90°C	Copper Tinned
TT1610	16.0mm <sup>2</sup>	Ø 10.5mm	42.0mm	M10		90°C	Copper Tinned
TT1612	16.0mm <sup>2</sup>	Ø 12.4mm	42.0mm	M12		90°C	Copper Tinned
TT165	16.0mm <sup>2</sup>	Ø 5.3mm	29.0mm	M5		90°C	Copper Tinned
TT166	16.0mm <sup>2</sup>	Ø 6.4mm	29.0mm	M6		90°C	Copper Tinned
TT168	16.0mm <sup>2</sup>	Ø 8.4mm	38.0mm	M8		90°C	Copper Tinned
TT2.5-4	2.5mm <sup>2</sup>	Ø 4.2mm	20.0mm	M4		90°C	Copper Tinned
TT2.5-5	2.5mm <sup>2</sup>	Ø 5.3mm	21.0mm	M5		90°C	Copper Tinned
TT2.5-6	2.5mm <sup>2</sup>	Ø 6.4mm	23.0mm	M6		90°C	Copper Tinned
TT2.5-8	2.5mm <sup>2</sup>	Ø 8.4mm	23.0mm	M8		90°C	Copper Tinned
TT2510R	25.0mm <sup>2</sup>	Ø 10.5mm	47.0mm	M10		90°C	Copper Tinned
TT2510	25.0mm <sup>2</sup>	Ø 10.5mm	47.0mm	M10		90°C	Copper Tinned
TT2512	25.0mm <sup>2</sup>	Ø 12.4mm	47.0mm	M12		90°C	Copper Tinned
TT255	25.0mm <sup>2</sup>	Ø 5.3mm	42.0mm	M5		90°C	Copper Tinned
TT256R	25.0mm <sup>2</sup>	Ø 6.4mm	42.0mm	M6		90°C	Copper Tinned
TT256	25.0mm <sup>2</sup>	Ø 6.4mm	42.0mm	M6		90°C	Copper Tinned
TT258R	25.0mm <sup>2</sup>	Ø 8.4mm	42.0mm	M8		90°C	Copper Tinned
TT258	25.0mm <sup>2</sup>	Ø 8.4mm	42.0mm	M8		90°C	Copper Tinned



Article	Wire size	Cross sec	eyelet	Length	For bolt	Operational degrees	Materials
TT3510R	35.0mm <sup>2</sup>	Ø 10.5mm	48.0mm	M10		90°C	Copper Tinned
TT3510	35.0mm <sup>2</sup>	Ø 10.5mm	48.0mm	M10		90°C	Copper Tinned
TT3512	35.0mm <sup>2</sup>	Ø 12.4mm	48.0mm	M12		90°C	Copper Tinned
TT356R	35.0mm <sup>2</sup>	Ø 6.4mm	43.0mm	M6		90°C	Copper Tinned
TT356	35.0mm <sup>2</sup>	Ø 8.4mm	43.0mm	M8		90°C	Copper Tinned
TT358R	35.0mm <sup>2</sup>	Ø 8.4mm	43.0mm	M8		90°C	Copper Tinned
TT358	35.0mm <sup>2</sup>	Ø 8.4mm	43.0mm	M8		90°C	Copper Tinned
TT4-5	4.0mm <sup>2</sup>	Ø 5.3mm	23.0mm	M5		90°C	Copper Tinned
TT4-6	4.0mm <sup>2</sup>	Ø 6.4mm	25.0mm	M6		90°C	Copper Tinned
TT4-8	4.0mm <sup>2</sup>	Ø 8.4mm	27.0mm	M8		90°C	Copper Tinned
TT5010R	50.0mm <sup>2</sup>	Ø 10.5mm	48.0mm	M10		90°C	Copper Tinned
TT5010	50.0mm <sup>2</sup>	Ø 10.5mm	48.0mm	M10		90°C	Copper Tinned
TT5012	50.0mm <sup>2</sup>	Ø 12.4mm	52.0mm	M12		90°C	Copper Tinned
TT5014	50.0mm <sup>2</sup>	Ø 14.0mm	52.0mm	M14		90°C	Copper Tinned
TT506	50.0mm <sup>2</sup>	Ø 6.4mm	48.0mm	M6		90°C	Copper Tinned
TT508R	50.0mm <sup>2</sup>	Ø 8.4mm	48.0mm	M8		90°C	Copper Tinned
TT508	50.0mm <sup>2</sup>	Ø 8.4mm	48.0mm	M8		90°C	Copper Tinned
TT6-10	6.0mm <sup>2</sup>	Ø 10.5mm	30.0mm	M10		90°C	Copper Tinned
TT6-5	6.0mm <sup>2</sup>	Ø 5.3mm	23.0mm	M5		90°C	Copper Tinned
TT6-6	6.0mm <sup>2</sup>	Ø 6.4mm	24.0mm	M6		90°C	Copper Tinned
TT6-8	6.0mm <sup>2</sup>	Ø 8.4mm	26.0mm	M8		90°C	Copper Tinned
TT7010R	70.0mm <sup>2</sup>	Ø 10.5mm	54.0mm	M10		90°C	Copper Tinned
TT7010	70.0mm <sup>2</sup>	Ø 10.5mm	54.0mm	M10		90°C	Copper Tinned
TT7012R	70.0mm <sup>2</sup>	Ø 12.4mm	54.0mm	M12		90°C	Copper Tinned
TT7012	70.0mm <sup>2</sup>	Ø 12.4mm	54.0mm	M12		90°C	Copper Tinned
TT7014	70.0mm <sup>2</sup>	Ø 14.0mm	63.0mm	M14		90°C	Copper Tinned
TT7016	70.0mm <sup>2</sup>	Ø 16.5mm	63.0mm	M16		90°C	Copper Tinned
TT708	70.0mm <sup>2</sup>	Ø 8.4mm	50.0mm	M8		90°C	Copper Tinned
TT9510	95.0mm <sup>2</sup>	Ø 10.5mm	60.0mm	M10		90°C	Copper Tinned
TT9512	95.0mm <sup>2</sup>	Ø 12.4mm	60.0mm	M12		90°C	Copper Tinned
TT9516	95.0mm <sup>2</sup>	Ø 16.5mm	67.0mm	M16		90°C	Copper Tinned
TT958	95.0mm <sup>2</sup>	Ø 8.4mm	60.0mm	M8		90°C	Copper Tinned
TT1610R	16.0mm <sup>2</sup>	Ø 10.5mm	42.0mm	M10		90°C	Copper Tinned
TT166R	16.0mm <sup>2</sup>	Ø 6.4mm	29.0mm	M6		90°C	Copper Tinned

